



### Guanghai PVC flexible tube details:

General PVC tubes are mainly used to transport liquids and insulation protection, mainly used in electronic, medical, communications, agriculture, fishery, and lighting etc. It has good acid, corrosion-resistant and fire retardan

Product Type	PVC tube
Material	PVC
Flame retardant	VW-1
Operation Temperature	-35°C-75°C
Withstand Voltage	600V
Specification	Customized
BPA Free	Yes
Working pressure(at room temperature)	2~2.5Pa
Feature	Light, Durable, Flexible, Soft etc
Usage	Transport liquid and gas, electronic, lighting
Place of Origin	Guangdong, China (Mainland)

## General size

Inner Diameters(mm)	Thickness(mm)	Outer Diameters (mm)	Material
Φ 1.0±0.1	0.30±0.05	Φ 1.6±0.1	PVC
Φ 1.5±0.1	0.35±0.05	Φ 2.2±0.1	PVC
Φ 2.0±0.1	0.50±0.05	Φ 3.0±0.1	PVC
Φ 2.5±0.1	0.50±0.05	Φ 3.5±0.1	PVC
Φ 3.0±0.1	0.50±0.05	Φ 4.0±0.1	PVC
Φ 3.5±0.1	0.50±0.05	Φ 4.5±0.1	PVC
Φ 4.0±0.1	0.50±0.05	Φ 5.0±0.1	PVC
Φ 4.5±0.1	0.50±0.05	Φ 5.5±0.1	PVC
Φ 5.0±0.1	0.50±0.05	Φ 6.0±0.15	PVC
Φ 5.5±0.1	0.50±0.05	Φ 6.5±0.15	PVC
Φ 6.0±0.1	0.50±0.05	Φ 7.0±0.15	PVC
Φ 6.5±0.1	0.50±0.05	Φ 7.5±0.2	PVC
Φ 7.0±0.1	0.50±0.05	Φ 8.0±0.2	PVC
Φ 7.5±0.1	0.50±0.05	Φ 8.5±0.2	PVC
Φ 8.0±0.1	0.50±0.05	Φ 9.0±0.2	PVC
Φ 8.5±0.1	0.50±0.05	Φ 9.5±0.2	PVC
Φ 9.0±0.1	0.50±0.05	Φ 10.0±0.2	PVC
Φ 9.5±0.1	0.50±0.05	Φ 10.5±0.2	PVC
Φ 10.0±0.1	0.50±0.05	Φ 11.0±0.2	PVC

Guanghai Electronic Insulation Materials Co.,Ltd professional in kind of insulation tubes and coated webbing ,  
any interested ,please contact us [info@gh-material.com](mailto:info@gh-material.com)



Address :(Plant) 3/F, No. 154, Huasheng East St.,  
Chenjiang Street, Zhongkai High-Tech Zone,  
Huizhou, Guangdong, China (Mainland)  
Tel/Fax:86-752-3175209  
Website: <http://www.gh-material.com>

