



Guanghai Non-slip heat shrink tubing details:

Heat resistant , High temperature ,Customized , Transparent .

Note : Not recommended for implantable or in-body uses or for continuous steam applications.

Product Type	Heat shrink tube
Material	Teflon
Flame retardant	VW-1
Operation Temperature	-70℃-200℃
Withstand Voltage	600V
Length	Customized
Shrink ratio	4:1
Working Pressure(at room temperature)	10-15KG
Breakdown strength	5KV/mm
Usage	Medical equipment,Household appliance ,Motors etc.
Place of Origin	Guangdong, China (Mainland)

General Size

Teflon(PTFE) Heat Shrink Tube Common Specification

Standard Specification(mm)	Inner Diameters Before Shrink(mm)	Average Thickness (mm)	Inner Diameters After Shrink (mm)
Φ 0.5	±0.2	0.10±0.05	≤0.4
Φ 0.8	±0.2	0.10±0.05	≤0.47
Φ 1.0	±0.2	0.10±0.05	≤0.66
Φ 2.0	±0.2	0.10±0.05	≤0.97
Φ 2.5	±0.2	0.10±0.05	≤1.32
Φ 3.0	±0.2	0.13±0.05	≤1.65
Φ 3.5	±0.2	0.13±0.05	≤1.83
Φ 4.0	±0.3	0.13±0.05	≤2.57
Φ 4.5	±0.3	0.13±0.05	≤3.1
Φ 5.0	±0.3	0.13±0.05	≤3.4
Φ 6.0	±0.3	0.13±0.05	≤3.8
Φ 6.5	±0.3	0.13±0.05	≤4.1
Φ 7.0	±0.3	0.13±0.05	≤4.2
Φ 7.5	±0.3	0.18±0.05	≤4.5
Φ 8.0	±0.3	0.18±0.05	≤4.8
Φ 8.5	±0.3	0.18±0.05	≤5.2
Φ 9.0	±0.3	0.18±0.05	≤5.3
Φ 9.5	±0.3	0.18±0.05	≤5.6
Φ 10.0	±0.3	0.18±0.05	≤6.2
Φ 10.5	±0.3	0.18±0.05	≤6.2
Φ 12	±0.3	0.18±0.05	≤6.95

Guanghai Electronic Insulation Materials Co.,Ltd professional in kind of insulation tubes and coated webbing , any interested ,please contact us info@gh-material.com

Address :(Plant) 3/F, No. 154, Huasheng East St.,
Chenjiang Street, Zhongkai High-Tech Zone,
Huizhou, Guangdong, China (Mainland)
Tel/Fax:86-752-3175209
Website: <http://www.gh-material.com>

